

Date 2024-12-12

Anchorage and use of anchor inside port

- **Anchorage areas:**
 - Oskarshamn (A) 1,5 nm S Furön N57 15.4 E016 36.6
 - Oskarshmn (B) 2,5 nm SE Furön N57 14.6 E016 39.2
- **Unsuitable areas:**
 - Close to fairway line
- **Prohibited areas:**
 - N/A
- **Use of anchor inside port:**
 - No limitations

Berth information and maximum dimensions

Flivik								
Berth	Cargo	Direction	Length (m)	Max Loa (m)	Max Boa (m)	Depth (m) acc. MVY	Max draft (m)	Remarks
1	RoRo	032 ⁰ / 212 ⁰	125m	120m	25m	6,0m	5.5m	

Tugboat information and requirements

- Tugboat normally not applicable
- **Escort tug requirements**
 - Normally not applicable
- **Bollard pull/Safe working load requirements - SWL (bollards and fairleads)**
 - No specific requirements, but vessel to have sufficient SWL for the current operation concerning weather and loading conditions
- **Local tugboat requirements**

Date 2024-12-12

Visibility restrictions

- Minimum visibility 1 nm

Daylight restrictions

- Only daylight

Wind restrictions

- All vessels 10 m/s mean wind

Source: According to SMHI/Bizmet and VIVA Simpevarp(SKB)

Wave and swell restrictions

- Normally not applicable

Current restrictions

- Normally not applicable

Two man pilotage

- Normally not applicable

Ice restrictions

- According to www.sjofartsverket.se/winternavigation.

Other restrictions

- Normally not applicable.